UV CLEAN AIR

GERM-KILLING HVAC UV LIGHT

The **UV Clean Air AHU** germicidal UV light system for central air systems features a robust design, durable construction and water-resistant components.

The auto-switching 120-277 VAC power supply is completely sealed for mounting in wet locations. In addition, the UV lamp cables incorporate a waterproof connector design with a 6' lead to allow safe routing of cables within the air handler.


The power supply is available with an optional 120 VAC plug.

BENEFITS

- Keeps air system cooling coils and interior surfaces free of mold
- Prevents slime build up in drain pan
- Improves energy efficiency
- Reduces need for air system maintenance
- Extends life of air system
- Kills airborne mold, bacteria, viruses
- Improves indoor air quality

FEATURES

- Single Dual Triple Quad lamp options
- Water-resistant shielded lamp design for stable UV operation
- High-efficiency electronic ballast for optimum lamp performance
- Automatic input voltage selection from 120 - 277 VAC 50/60 Hz.
- Lifetime Warranty on all parts except lamp(s)








Magnetic "Z" Bracket for Easier Installation

Installation of UV lamps has never been easier! Our convenient Magnetic "Z" Bracket eliminates the need for drilling, precise measuring, and fumbling with small screws in the tight confines of the air handler - in fact no tools are required at all to install the bracket!



GERM-KILLING HVAC UV LIGHT



Comprehensive Air Purification

Combine **UV Clean Air PCO** or **UV Clean Air PCO RT** with **UV Clean Air AHU germicidal UV Light** for comprehensive whole-house air purification. UV Clean Air PCO/Activated Carbon Cells neutralize odors and toxic VOCs.

PART NUMBERS			
AHU Series 1 1 Year Lamp (s)		Power Supply	
	CA-100S-l (single) CA-100D-l (dual) CA-100T-l (triple) CA-100Q-l (quad)	TUVP-1S TUVP-1D-I TUVP-1T TUVP-1Q-I	
AHU Series 1 2 Year Lamp (s)	CA-200S-I (single) CA-200D-I (dual) CA-200T-I (triple) CA-200Q-I (quad)	TUVP-1S TUVP-1D-I TUVP-1T TUVP-1Q-I	
Wall Plug	ADD "P" for wall plug Example: TUV-100S-I-P		
Replacement Lamps	TUVL-115 (1 year) TUVL-215 (2 year)		

SPECIFICATIONS

DOWAR SUDD	ly Cinala	9. Dual (TUVP-1S/1D-I)
rower subb	w - Siliule	' Q Duai l	1 U V P - 1 3/ 1 D - 1 1

Auto switching multi-voltage 0.51A /120V Thru 0.22A /277Vs

Dimensions 8.75"L x 3.5"W x 2.5"D

Power Supply - Triple & Quad (TUVP-1T/1Q-I)

Electrical Auto switching multi-voltage 1.02A /120V Thru 0.44A /277V

Dimensions 13"L x 3.5"W x 2.5"D

UV-C Lamp - 1 Year (TUVL-115)

Spectrum254 nm Germicidal UV-CTypeUnshielded Quartz Hot FilamentDimensions15"L x 0.74" Dia.

UV-C Lamp - 2 Year (TUVL-215)

Spectrum 254 nm Germicidal UV-C Type Shielded Quartz Hot Filament Dimensions 15"L x 1" Dia.

COMMON TO ALL

Kit Includes

Power Supply (NEMA IP54), UV Lamp(s), 6' Lamp
Cable, 6' Power Cord, Lamp Mounting Brackets,
Mounting Hardware and Panel Indicator

Warranty Lifetime for all parts except lamp

Cerifications





*For CE compliant parts add -CE to the part number Example: CA-100S-I-CE







Made in USA